



ORLEN OIL TRAWOL 2T

QUALITY CLASS: API: TC

GENERAL FEATURES:

Semisynthetic oil perfectly mixing with fuel, guaranteeing high protection against carbon depositing and very low smoke emission, in every working conditions it keeps lubricating oil film protecting the engine against wearing out at high revolution value and in high temperature.

APPLICATION:

ORLEN OIL Trawol 2T is intended for two-stroke engines of garden equipment of any kind. It is mainly intended for mowers, saws, etc. of various manufacturers including Husqvarna and Stihl.

Dosage:

As recommended by the engine manufacturer.

2% of the fuel volume /1:50/ unless otherwise recommended by the engine manufacturer.

It will be provided in 100 ml packaging with a rule on the label to facilitate oil dosage in fuel.

PHYSICAL AND CHEMICAL PROPERTIES:

Parameters	Units	Typical values
kinematic viscosity at 100°C	mm ² /s	9.7
flow temperature	°C	-25
ignition temperature	°C	104
sulphate ash	%	0.17
content of solid foreign bodies	%	no content
water content	% (V/V)	no content

Note: The above values of physical and chemical properties are typical values. Actual values are specified in quality certificates enclosed with each product lot.

VERSION:

1 / 2023.07.17

