

LUBRICATORS, OIL LEVEL SIGHT GLASSES

Oil level sight glasses



75 041 500

TECHNICAL DATA

- Material inspection glass: glass
- Housing material: aluminium

PACKAGING

- Packing unit: 1

PRODUCTS

Item-No.	Description 1	Description 2	Connection	SW (mm)	Pressure (bar)	Temperature range (°C)
75 038 500	Oil level sight glass Alu-250°C-10 bar	G 1/4" -SK-17 mm-glass	G 1/4" male	17	10	250
75 039 500	Oil level sight glass Alu-250°C-10 bar	G 3/8" -SK-22 mm-glass	G 3/8" male	22	10	250
75 040 500	Oil level sight glass Alu-100°C-4 bar	G 1/2" -SK-27 mm-glass	G 1/2" male	27	4	-20 / +100
75 041 500	Oil level sight glass Alu-100°C-4 bar	G 3/4" -SK-32 mm-glass	G 3/4" male	32	4	-20 / +100
75 042 500	Oil level sight glass Alu-100°C-4 bar	G 1" -SK-41 mm-glass	G 1" male	41	4	-20 / +100
75 043 500	Oil level sight glass Alu-100°C-4 bar	G 1 1/4" -SK-50 mm-glass	G 1 1/4" male	50	4	-20 / +100
75 044 500	Oil level sight glass Alu-100°C-4 bar	G 1 1/2" -SK-55 mm-glass	G 1 1/2" male	55	4	-20 / +100
75 045	Oil level sight glass Alu-100°C-4 bar	G 2" -SK-70 mm-glass	G 2" male	70	4	-20 / +100

Abbreviations

a	Outer / Male
G	Whitworth Pipe Thread, cylindrical, ISO 228 (DIN 259)
SK	Hexagon
SW	Wrench size